GGRXCB03TA

GROXX STEEL D-SHAPE CARABINER, TRIPLE LOCK (ANSI), 25 MM GATE



OVERVIEW

The Groxx steel d-shape carabiner (GGRXCB03TA) is a connector for fall protection systems, hot-forged from high-tensile steel with an auto-locking triple-action gate. Major axis strength is 30 kN. It links harnesses, lanyards, rope grabs, self-retracting lifelines and anchor points.

KEY FEATURES

- **Triple Lock**: auto-locking triple-action gate.
- 30 kN major axis.
- **25 mm gate opening**: wide enough for scaffold tubes and large anchor eyes.
- **3,600 lbf gate strength**: for ANSI Z359.12 applications.
- Yellow zinc / white zinc finish for corrosion resistance; customisable Groxx laser marking.

TECHNICAL SNAPSHOT

PARAMETER	GGRXCB03TA
EN requirement	Min. 20 kN major axis (gate closed and locked), 15 kN gate closed but unlocked, 7 kN minor axis
Material	High Tensile Steel Alloy
Shape	D-Shape
Gate	Triple Lock
Breaking strength, major axis	30 kN / 6742 lbf
Gate strength	3600 lbf
Gate opening	25 mm
Length	114 mm
Width	73 mm
Weight	251 g
Finish	Yellow zinc / white zinc
Marking	Groxx model code, batch number, strength ratings, standard

INSTALLATION & USE

Check before every use that the gate opens freely, closes fully on its own and locks completely.

Load only along the major axis. Avoid side loading, three-way loading and loading over an edge or across the gate.

Withdraw from use after a fall, or if there is any crack, deformation, sharp wear or corrosion.

A competent person must carry out a detailed periodic inspection at least every 12 months, and record it.

STANDARDS

EN 362 Class B

Designed to EN 362 Class B. Test certificate on request. Important: always check that the gate is fully closed and locked before use. Never load the carabiner across the gate or over an edge.

FULL DATA SHEET ↗

Product page ↗