GGRXFBH102

GROXX FULL BODY HARNESS, 1-POINT, FORGED D-RING



OVERVIEW

The Groxx Full Body Harness, 1-Point, Forged D-Ring (GGRXFBH102) is a full body harness made to EN 361. It is built from 45 mm high-tenacity polyester webbing with forged steel D-ring, stamped steel buckles, in one universal size that adjusts to fit most workers. General construction, scaffolding, roofing and maintenance where a single dorsal fall arrest point is needed.

KEY FEATURES

- **Attachment**: Dorsal (back) forged steel D-ring.
- Dual-colour webbing: shoulder straps and thigh straps in contrasting colours so the harness is put on the right way up, first time.
- Sit strap under the seat to support the user in suspension after a fall.
- Padded back plate keeps the dorsal D-ring upright and easy for a colleague to connect.
- **3 adjustment points**: Chest strap (length and position), left thigh strap, right thigh strap.

TECHNICAL SNAPSHOT

PARAMETER	GGRXFBH102
EN requirement	Static 15 kN at fall-arrest attachment points; dynamic drop test with 100 kg mass
Attachment points	1: Dorsal (back) forged steel D-ring
Adjustment points	3
Webbing	45 mm high-tenacity polyester
Hardware	Forged steel D-ring, stamped steel buckles
Size	Universal (one size, adjustable)
Maximum user weight	100 kg including tools and equipment
Marking	Groxx model code, serial/batch number, standard, date of manufacture
Inspection	Before every use; detailed inspection by a competent person every 12 months

INSTALLATION & USE

Inspect the harness before every use: webbing for cuts, burns, fraying or chemical damage; stitching for broken or pulled threads; D-rings and buckles for cracks, distortion or corrosion.

A competent person must carry out a detailed periodic inspection at least every 12 months, and record it. Groxx ASMA can schedule and record these inspections.

Withdraw the harness from use immediately after it has arrested a fall.

Clean with lukewarm water and mild soap, dry naturally away from direct heat and sunlight, and store in a dry, ventilated place.

Have a rescue plan in place before work starts. Suspension after a fall must be kept as short as possible.

STANDARDS

EN 361

FULL DATA SHEET ↗

Product page ↗