GGRXFBH204

GROXX FULL BODY HARNESS, 2-POINT, HI-VIS, WITH WAIST BELT AND TOOL BAG



OVERVIEW

The Groxx Full Body Harness, 2-Point, Hi-Vis, with Waist Belt and Tool Bag (GGRXFBH204) is a full body harness made to EN 361. It is built from 45 mm high-tenacity polyester webbing with stamped steel D-rings and buckles, in one universal size that adjusts to fit most workers. Installers and maintenance staff on busy sites who carry tools and need front and back attachment.

KEY FEATURES

- **Attachment**: Dorsal (back) D-ring; Front sternal attachment (two D-rings, marked A/2, used together).
- High-visibility green webbing.
- Integrated waist belt with tool bag.
- Front and back fall arrest attachment.
- **5 adjustment points**: Left shoulder strap, right shoulder strap, waist belt, left thigh strap, right thigh strap.

TECHNICAL SNAPSHOT

PARAMETER	GGRXFBH204
EN requirement	Static 15 kN at fall-arrest attachment points; dynamic drop test with 100 kg mass
Attachment points	2: Dorsal (back) D-ring; Front sternal attachment (two D-rings, marked A/2, used together)
Adjustment points	5
Webbing	45 mm high-tenacity polyester
Hardware	Stamped steel D-rings and buckles
Size	Universal (one size, adjustable)
Maximum user weight	100 kg including tools and equipment
Marking	Groxx model code, serial/batch number, standard, date of manufacture
Inspection	Before every use; detailed inspection by a competent person every 12 months

INSTALLATION & USE

Inspect the harness before every use: webbing for cuts, burns, fraying or chemical damage; stitching for broken or pulled threads; D-rings and buckles for cracks, distortion or corrosion.

A competent person must carry out a detailed periodic inspection at least every 12 months, and record it. Groxx ASMA can schedule and record these inspections.

Withdraw the harness from use immediately after it has arrested a fall.

Clean with lukewarm water and mild soap, dry naturally away from direct heat and sunlight, and store in a dry, ventilated place.

Have a rescue plan in place before work starts. Suspension after a fall must be kept as short as possible.

STANDARDS

EN 361

> Note: The waist belt and tool bag are for comfort and carrying tools only. They are not a work positioning belt.

FULL DATA SHEET ↗

Product page ↗