GGRXHL602

GROXX HARNESS AND TWIN LANYARD KIT, HI-VIS, WITH FRONT D-RINGS



OVERVIEW

The Groxx Harness and Twin Lanyard Kit, Hi-Vis, with Front D-Rings (GGRXHL602) is a full body harness made to EN 361 / EN 355. It is built from 45 mm high-tenacity polyester webbing with stamped steel hardware, in one universal size that adjusts to fit most workers. Ready-to-issue fall arrest kit for busy sites.

KEY FEATURES

- **Attachment**: Dorsal (back) D-ring with factory-fitted twin energy-absorbing lanyard; Front sternal attachment (two D-rings, marked A/2, used together).
- High-visibility harness with front D-rings and a twin-leg energy-absorbing lanyard (28 mm webbing, maximum 2.0 m).
- Two large-gate hooks for 100% tie-off.
- Waist belt with tool bag.
- **4 adjustment points**: Chest strap, waist belt, left thigh strap, right thigh strap.

TECHNICAL SNAPSHOT

PARAMETER	GGRXHL602
EN requirement	Harness static 15 kN; lanyard braking force max. 6 kN, extension max. 1.75 m
Attachment points	2: Dorsal (back) D-ring with factory-fitted twin energy-absorbing lanyard; Front sternal attachment (two D-rings, marked A/2, used together)
Adjustment points	4
Webbing	45 mm high-tenacity polyester
Hardware	Stamped steel hardware
Size	Universal (one size, adjustable)
Maximum user weight	100 kg including tools and equipment
Lanyard	Twin-leg, 28 mm polyester webbing, maximum length 2.0 m, EN 355 energy absorber
Marking	Groxx model code, serial/batch number, standard, date of manufacture
Inspection	Before every use; detailed inspection by a competent person every 12 months

INSTALLATION & USE

Inspect the harness before every use: webbing for cuts, burns, fraying or chemical damage; stitching for broken or pulled threads; D-rings and buckles for cracks, distortion or corrosion.

A competent person must carry out a detailed periodic inspection at least every 12 months, and record it. Groxx ASMA can schedule and record these inspections.

Withdraw the harness from use immediately after it has arrested a fall.

Clean with lukewarm water and mild soap, dry naturally away from direct heat and sunlight, and store in a dry, ventilated place.

Have a rescue plan in place before work starts. Suspension after a fall must be kept as short as possible.

STANDARDS

EN 361 EN 355

FULL DATA SHEET ↗

Product page ↗