GGRXWPB101

GROXX WORK POSITIONING BELT, PADDED, 2 LATERAL D-RINGS



OVERVIEW

The Groxx work positioning belt (GGRXWPB101) is an EN 358 belt with a wide padded back support and two lateral D-rings. Used with an adjustable positioning lanyard, it holds the worker at the work point with both hands free. It is rated for a user of up to 150 kg.

KEY FEATURES

- **Wide padded back support**: with breathable mesh lining, for comfort during long positioning tasks.
- **Two lateral steel D-rings**: for an EN 358 positioning lanyard.
- Stamped steel buckle and webbing keepers for a secure fit.
- **Rated for 150 kg**: user weight.

TECHNICAL SNAPSHOT

PARAMETER	GGRXWPB101
EN requirement	Static 15 kN; work positioning only, not for fall arrest
Attachment points	2 lateral D-rings
Webbing	High-tenacity polyester
Back support	Padded, mesh-lined
Hardware	Steel D-rings, stamped steel buckle
Maximum user weight	150 kg
Marking	Groxx model code, serial/batch number, standard, date of manufacture

INSTALLATION & USE

Inspect the harness before every use: webbing for cuts, burns, fraying or chemical damage; stitching for broken or pulled threads; D-rings and buckles for cracks, distortion or corrosion.

A competent person must carry out a detailed periodic inspection at least every 12 months, and record it. Groxx ASMA can schedule and record these inspections.

Withdraw the harness from use immediately after it has arrested a fall.

Clean with lukewarm water and mild soap, dry naturally away from direct heat and sunlight, and store in a dry, ventilated place.

STANDARDS

EN 358

> Important: a work positioning belt is not fall arrest equipment. Never use it to arrest a fall. Wear it with a full body harness and a fall arrest system whenever there is a risk of falling.

FULL DATA SHEET ↗

Product page ↗