GGSM005

SWAGELESS CABLE EXTREMITY

Also used in OL VL



OVERVIEW

Swageless cable extremity for 8 mm 7x19 wire rope. The high-grade stainless steel termination fits without swaging tools and gives a clean, streamlined finish with no frayed wire ends.

KEY FEATURES

- **Swageless Termination**: The cable extremity features a high-grade stainless steel attachment designed for a secure, tool-free termination that integrates seamlessly with mating components.
- **Clean Finish**: Swageless crimping ensures a streamlined connection, effectively eliminating frayed wire ends for enhanced safety and a professional aesthetic.

TECHNICAL SNAPSHOT

PARAMETER	GGSM005
Component	Material
Cable Extremity & Housing	316 Grade Stainless Steel
Poker Pin	Brass
EN requirement	Static test 12 kN (18 kN if any load-bearing part is non-metallic), +1 kN per additional user (CEN/TS 16415)
Minimum Breaking Strength (MBS)	25 kN (approx. 5,620 lbs)

USE & INSPECTION

Install to the Groxx instructions by trained installers. Inspect before each use and at least every 12 months by a competent person.

STANDARDS

EN 795:2012 Type C | CEN/TS 16415

Designed to EN 795:2012 Type C, CEN/TS 16415. Test certificate on request.

FULL DATA SHEET ↗

Product page ↗