GGWLG061

WEBSAFE LIFEGUARD TEMPORARY LIFELINE



OVERVIEW

The Groxx Websafe Lifeguard (GGWLG061) is a high-mobility, synthetic horizontal lifeline system engineered for rapid deployment and temporary fall protection. Designed for work sites where permanent anchorage is not yet established, this textile-based system provides a secure, continuous anchorage line between two structural points. It is an essential solution for construction, maintenance, and short-term industrial projects requiring immediate, reliable safety infrastructure.

KEY FEATURES

- **Rapid Deployment Tensioning**: The system features an integrated heavy-duty Ratchet Tensioner, allowing users to easily achieve the required line tension between structures without the need for specialized tools.
- **Extended Span Capability**: With a maximum span length of up to 20.0 meters, the GGWLG061 offers an expansive safe working zone, reducing the need for frequent re-positioning of anchorage points.
- **Complete Anchorage Kit**: Each system includes two Cross Arm Straps, providing a versatile "tie-off" solution that can be wrapped around various structural members (beams, columns, or pillars) to create secure end-terminations.
- **High-Strength Webbing**: Constructed from premium 30mm Polyester Webbing, the lifeline is designed to withstand the rigors of outdoor use while remaining lightweight and easy to transport in a gear bag.

TECHNICAL SNAPSHOT

PARAMETER	GGWLG061
Model Number	GGWLG061
Webbing Material	30.0 mm High-Tenacity Polyester
EN requirement	Static test 12 kN (18 kN if any load-bearing part is non-metallic), +1 kN per additional user (CEN/TS 16415)
Maximum Span	20.0 meters
Attachment Ends	Stitched Loops with Twist-Lock Karabiners
User Rating	Up to 2 Users
System Weight	4.12 kg (± 0.05 kg)

INSTALLATION & USE

Universal Tie-Off: The included Cross Arm Straps allow the system to be anchored to any structure capable of withstanding the required fall arrest loads.

Dual-Action Security: The ends of the lifeline are equipped with high-strength Stitched Loops and Twist-Lock Karabiners, ensuring a secure, vibration-resistant connection to the anchorage straps.

Ease of Transport: At just over 4 kg, the entire system is highly portable, making it the preferred choice for contractors moving between multiple work sites.

STANDARDS

EN 795:2012 Type B | CEN/TS 16415

> The Websafe Lifeguard GGWLG061 eliminates the complexity of temporary fall protection. By combining a high-leverage ratchet system with durable polyester webbing, Groxx provides a "plug-and-play" safety solution that balances extreme portability with industrial-grade strength.

FULL DATA SHEET ↗

Product page ↗