GRXOIP800

ENTRY PIPE



OVERVIEW

The Groxx GRXOIP800 is a heavy-duty wire rope guide pipe set engineered specifically for 800 kg capacity traction hoists. Installed at the entry and exit apertures of the hoist housing, these precision-formed tubes direct the wire rope smoothly into and out of the internal drive chamber.

KEY FEATURES

- **Flared Bell-Mouth Ends**: Engineered with smooth, flared radii at the entry and exit mouths to allow multi-directional rope movement without shearing or scoring the cable.
- **Heavy-Wall Wear Resistance**: Built with thick-walled metal construction to endure high-velocity wire rope friction over extended operational periods.
- **Corrosion-Proof Passivation**: Treated to resist severe atmospheric exposure, rust, and chemical contamination on active construction and maintenance sites.
- **Direct-Fit Mounting Interface**: Features pre-machined mounting flanges/threads for quick, secure attachment during routine hoist maintenance or field replacement.

TECHNICAL SNAPSHOT

PARAMETER	GRXOIP800
Part Number	GRXOIP800
Rated Hoist Capacity	800 kg Traction Hoist Systems
Compatible Rope Diameter	8.3 mm to 9.5 mm Wire Rope
Primary Material	Heavy-Wall AISI 316 Stainless Steel / Hardened Steel
Surface Finish	Smooth-Bore Polished / Electro-Passivated
Configuration	Dual-Piece Set (Inlet Guide Pipe + Outlet Guide Pipe)
Weight	0.68 kg (Combined Set)

USE & INSPECTION

Install to the Groxx instructions by trained installers. Inspect before each use and at least every 12 months by a competent person.

STANDARDS

See product page

> The GRXOIP800 Guide Pipe Set preserves the structural integrity of your suspended access hoists.

FULL DATA SHEET ↗

Product page ↗