

WEBSAFE LIFEGUARD

GGWLG061

GROXX

TECHNICAL SPECIFICATION

The Groxx Websafe Lifeguard is a temporary webbing lifeline system designed for restraint or fall arrest use when working near exposed edges. It enables users to move safely along the span while maintaining continuous protection.

FEATURES

- Integrated ratchet tensioner for quick and easy tightening between two anchor structures
- Supplied with two cross arm straps for secure tie-off
- Delivered in a permanently attached carry bag for convenient storage and transport
- Allows lanyard connection via karabiners for safe movement along the lifeline
- Designed for use by up to two workers simultaneously
- Webbing: 30 mm polyester, minimum breaking strength (MBS) 25 kN
- Cross Arm Strap: 44 mm polyester, MBS 25 kN
- Karabiners: Galvanized alloy steel with silver passivation, MBS 40 kN
- Ratchet Tensioner: Carbon steel with silver passivation, MBS 15 kN



MATERIAL

- ED Coated High Strength Alloy Steel

WEIGHT & HEIGHT

- 4.120 kg $\pm$ 0.05 kg

MINIMUM BREAKING STRENGTH

- Minimum Breaking Strength: 25 kN
- Minimum Span: 5 m
- Maximum Span: 20 m

CE EN 795:2012 TS
16415:2013 Type B &
C (for up to 2 users)

USED IN INDUSTRY

